



RACK 19" cabinets - floor standing, ready-to-assemble

EN

CODE: RS2768GD

v1.0/II

NAME: RACK cabinet, floor standing, ready-to-assemble 27U/600x800



INTENDED USE

The RACK 19" cabinet enables integrating CCTV, AC, I&HAS, RTV, LAN, or other systems in medium and big companies. It is intended for devices manufactured in enclosures of the 19" standard. Due to the RACK cabinets, the devices are aesthetically mounted and protected against mechanical damage.

SPECIFICATIONS

Mounting dimensions:	W=19", H=27U
External dimensions:	W=600, H=1388, D=800 [mm, +/-2]
Net/gross weight:	74 / 78,9 [kg]
Materials:	<ul style="list-style-type: none">- RACK mounting rails: cold-rolled steel SPCC 2mm RAL 9004 - bolted- horizontal mounting rails: cold-rolled steel SPCC 1,5mm RAL 9004 - bolted- frame: cold-rolled steel SPCC 1,2mm RAL 9004 - welded- front door: 5mm toughened glass / SPCC 1,2mm RAL 9004 - hinged- side panel ; cold-rolled steel SPCC 1,2mm RAL 9004 - removable- rear door: cold-rolled steel SPCC 1,2mm RAL 9004 - hinged
Static load:	800 kg (with leveling feet)
Use:	inside, IP20
Notes:	<ul style="list-style-type: none">- adjustable distance between front and rear RACK rails- ventilation holes in the front door, top and bottom panel- possible mounting of a 4-fan tray in the top panel - RAWP800- cable ducts in the top and bottom panel- 4 casters without locks and 4 leveling feet included- possible assembly of a 100mm high plinth - RAC168- lockable front door (2 keys in set)- lockable rear door (2 keys in set)- side panel - lock assembly possible - RAZB16- the possibility of installing a set of RAPU-S grounding wires in the rack- ready-to-assemble
Certificates, declarations:	RoHS